Amendments to the Claims

Claim 1 (currently amended): A scanner comprising:

a ~~transparent scanning~~ window;

a housing, the housing including an inside, an outside, a first side supporting the ~~scanning~~ window, having an inside surface and having an outside surface, and a second side having an inside surface opposite the inside surface of the first side and having an outside surface;

a scanning array movable in the housing relative to the ~~scanning~~ window along a scanning path, the scanning array generally facing the inside surface of the first side; and

~~a light source movable with the scanning array, the light source generally facing the first side; and~~

a calibration target supported inside ~~by~~ the housing within the scanning path, on the inside surface of the first side and spaced apart from the window, the calibration target generally facing the inside surface of the second side, in operation.

A1

Claim 2 (cancelled).

Claim 3 (original): A scanner in accordance with claim 1 wherein the scanning array is a color capable scanning array.

Claim 4 (original): A scanner in accordance with claim 3 and further comprising a monochrome printer commonly housed with the scanner in the housing.

Claim 5 (original): A scanner in accordance with claim 1 wherein the target is a color target.

Claim 6 (original): A scanner in accordance with claim 1 wherein the target is a black target.

Claim 7 (currently amended): A scanner in accordance with claim 1 wherein the target is a color target, wherein the scanner further includes second and third color calibration targets supported inside the housing from the first side, proximate the ~~scanning~~ window and within the scanning path, the second and third calibration targets facing the second side, and wherein the scanner is configured to use the first mentioned and second and third color calibration targets for color registration.

Claim 8 (original): A scanner in accordance with claim 1 and further including a motor configured to move the scanning array along the scanning path, a power switch, coupled to the scanning array and the motor, for turning the scanner on and off, and logic circuitry coupled to the power switch, the scanning array, and the motor, and configured to effect movement of the scanning array to scan the calibration target in response to the scanner being turned on.

Claim 9 (currently amended): A scanner in accordance with claim 8 wherein the target is a color target, wherein the scanner further includes second and third color calibration targets inside the housing, on the inside surface of the first side and spaced apart from the window, wherein the logic circuitry is further configured to perform a calibration in response to scanning the first mentioned, second, and third color calibration targets.

Claim 10 (currently amended): A method of manufacturing a scanner, the method comprising:

providing a scanner including a ~~transparent scanning~~ window; a housing, the housing including an inside, an outside, a first side supporting the ~~scanning~~ window, having an inside surface and having an outside surface, and a second side having an inside surface opposite the first side and having an outside surface; a scanning array movable in the housing relative to the ~~scanning~~ window along a path, the scanning array facing the inside surface of the first side; and a light source movable with the scanning array and facing the first side in operation; and

~~supporting~~ permanently providing, prior to delivery to an end user, a calibration target inside ~~from~~ the housing, on the inside surface of the first side, within the scanning path, the calibration target facing the second side.

Claim 11 (cancelled).

Claim 12 (original): A method in accordance with claim 10 wherein the scanning array is color capable.

Claim 13 (original): A method in accordance with claim 12 and further comprising commonly housing a monochrome printer with the scanner in the housing.

Claim 14 (original): A method in accordance with claim 10 wherein supporting a calibration target comprises supporting a color target.

Claim 15 (original): A method in accordance with claim 10 wherein supporting a calibration target comprises supporting a black target.

Claim 16 (currently amended): A method in accordance with claim 10 wherein supporting a target comprises supporting at least three different color calibration targets inside the housing from the first side, proximate the ~~scanning~~ window and within the scanning path, facing the second side, the method further comprising using the color calibration targets for color registration.

Claim 17 (original): A method in accordance with claim 10 and further comprising effecting scanning of the calibration target by the scanning array in response to the scanner being powered-up.

Claim 18 (original): A method in accordance with claim 17 and further comprising calibrating the scanner in response to scanning of the color calibration targets.

Claim 19 (currently amended): A multifunction device comprising:

a housing having a first side and a second side opposite the first side;

a monochrome printer supported in the housing; and

a color flatbed scanner supported in the housing, the scanner including~~,~~ a sub-housing having an inside, an outside, a top side having an inside

surface and an outside surface ~~first side~~, and a bottom ~~second~~ side opposite the top ~~first~~ side and having an inside surface and an outside surface, the scanner including ~~an imaging area including~~ a ~~transparent~~ window ~~surface~~, supported by the top ~~first~~ side of the sub-housing, a scanning array movable in the sub-housing relative to the window ~~imaging area~~ along a scanning path, the scanning array generally facing the inside surface of the top ~~first~~ side so as to be able to scan the window ~~imaging area~~, first, second, and third color ~~a~~ calibration targets ~~target~~ supported inside the housing, attached to the inside surface of the top side, spaced apart from the window, ~~from the first side~~, ~~proximate the imaging area and~~ within the scanning path, the calibration targets ~~target~~ facing the inside surface of the bottom ~~second~~ side, a motor configured to move the scanning array along the scanning path, a power switch, coupled to the scanning array and the motor, for turning the scanner on and off, and logic circuitry coupled to the power switch, the scanning array, and the motor, and configured to effect movement of the scanning array to scan the calibration targets ~~target~~ in response to the scanner being turned on.

Claim 20 (currently amended): A multifunction device in accordance with claim 19 wherein the logic circuitry is further configured to perform a calibration in response to scanning the first ~~mentioned~~, second, and third color calibration targets.